



## Applications

Instarmac Permanent Pothole Repair® is a suitable solution for roads, pavements, driveways and parking lots. The product can be trafficked instantly in wet, freezing and hot conditions and at the same time is compatible with the existing road surface. Instarmac Permanent Pothole Repair® can be applied at depths up to 50mm. (Greater depths can be achieved by applying the layer-on-layer method).

## Technical

Instarmac Permanent Pothole Repair® includes fully graded, high PSV interlocking aggregate and specially formulated bitumen and is supplied in recyclable 22.5kg/50lb containers.

## Recommended Application

Pothole repairs can be achieved at any depth.

1. Ensure pothole is free of debris and standing water.
2. Apply Instarmac SCJ spray sealant to pothole edges.
3. Apply the product slightly proud of the pothole.
4. Compact with a hand tamper, or suitable mechanical alternative.

## Storage

Store inside above 5°C/41°F.

## Shelf Life

Shelf life in correct conditions for sealed goods is 6 months. Delivered on shrink wrapped pallets.

## Handling Guidelines

Instarmac Permanent Pothole Repair® is manufactured and delivered within as short a time as possible to ensure fresh easy to lay material is supplied. It should be noted, if storage guidelines are not followed the material can appear stiff. By placing point load pressure on the bag, you will regain workability.

## Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing

and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from Da-Lee.

## Quality Assurance

Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold to our conditions of sale, copies of which can be obtained on request.

## Technical Data

PSV	60
Colour	Black
Coverage	Approx 1m <sup>2</sup> at 12-15mm compacted, depending on the surface regularity of the reinstatements.

## Contact Us

Da-Lee Group, 350 Jones Road, Stoney Creek, ON L8E 5N2, Canada  
Tel: 905 643 1135 Email: [contact@daleegroup.com](mailto:contact@daleegroup.com) Website: [daleegroup.com](http://daleegroup.com)